

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 05-097884

(43)Date of publication of application : 20.04.1993

(51)Int.Cl.

C08G 63/66

C08G 63/685

C08G 69/48

C09K 3/16

(21)Application number : 03-260731

(71)Applicant : DAICEL CHEM IND LTD

(22)Date of filing :


08.10.1991

(72)Inventor : WATANABE ICHIRI

OSAGAWA ICHIRO

NAKADA TATSUYA

(54) HIGH POLYMER BASED ANTISTATIC AGENT



(57)Abstract:

PURPOSE: To obtain a high polymer based antistatic agent consisting of a specific graft polymer and capable of providing excellent antistatic property, gloss, chemical resistance, oil resistance, etc., to a resin for molding without impairing physical properties of the resin for molding by blending with the resin for molding in a proper amount.

CONSTITUTION: An antistatic agent for thermoplastic resin expressed by formula I or formula II [R¹ is 4-8C alkylene group or phenylene group which may have a substituent group; R² is 4-14C alkylene group; R³ is 2-6C alkylene group;

(m) is 1-1000 and (n) is 1-10 and (p) is 1-200 and (q) is integer of 1-500] and composed of a graft polymer in which the trunk polymer is composed of polyamide and the branch polymer is composed of a block polymer of a polyalkylene ether and thermoplastic polyester. The antistatic agent is produced by e.g., reacting a polyamide with 2-4C alkylene oxide in the presence of an alkaline compound to afford a β -hydroxyalkylated polyamide and polycondensing the resultant modified polyamide with a polyester prepolymer of formula III (μ is integer of 1-200).